



AIRMAN - HIGH CUT

Article No.: 73108CV208

Model No.: 8324-2

Cavalier™ Airman Safety Footwear is designed to offer optimum comfort during long work hours. PU sole which is anti-skid and alkali resistant. Suitable for any nature of harsh working conditions. High-cut safety shoes provided with inner lining along with high sweat adsorption property for a dry feel and an extra cushioned soft molded in sock for extreme comfort.



Moisture
Absorbing
Insoles



IMPACT
RESISTANT



PENETRATION
RESISTANT



SLIP
RESISTANT



OIL
RESISTANT



ELECTRICAL
HAZARD PREVENT

Category Description

S1P 200 Joule Toecap Protection. Closed seat region (fully enclosed heel). Antistatic properties. Energy absorption of seat region.

Doc. Control:	Rev.:	Date:
	3.2	April 9, 2016

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT FW 9008-3.2



COMPOSITION:

- Safety Boots S1P, without laces, made in bovine printed leather
- Good Design, comfortable, antislip, light and flexible
- Breathable lining
- Welder protection and velcro

FEATURES:

Upper:	Bovine Printed leather
Lining:	Breathable with high steaming permeability to improve comfort.
Toe-Cap:	Steel Toe Cap
Antiperforation:	Stainless Steel
Insock:	Antistatic with Antibacterial Treatment
Width:	10 Mondopoint
Norm:	EN ISO 20345:2011 CE
Category:	S1P SRC
Color:	Black
Sizes:	36-48 (Europe)



STEEL TOE CAP



ANTIPERFORATION

BORN TOUGH

A PRODUCT OF





AIRMAN - HIGH CUT

Article No.: 73108CV208

Model No.: 8324-2

AIRMAN

TECHNICAL SPECIFICATIONS



Category Description

S1P 200 Joule Toecap Protection. Closed seat region (fully enclosed heel). Antistatic properties. Energy absorption of seat region.

Doc. Control:	Rev.:	Date:
	3.2	April 9, 2016

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT FW 9008-3.2

BORN TOUGH

