



### CAPTAIN - HIGH CUT

Article No.: 73110CV214

Model No.: 8713-4

Cavalier™ Captain Safety Footwear is designed to offer optimum comfort during long work hours. PU sole which is anti-skid and alkali resistant. Suitable for any nature of harsh working conditions. High-cut safety shoes provided with inner lining along with high sweat adsorption property for a dry feel and an extra cushioned soft molded in sock for extreme comfort.



#### COMPOSITION:

- Safety Shoes S3 made in waterproof smooth leather
- 100% Metal Free
- Good design, comfortable, antislip, light and flexible top quality leather, superior resistant to hard conditions

#### FEATURES:

<b>Upper:</b>	Waterproof Smooth Leather
<b>Lining:</b>	Breathable with high steaming permeability to improve comfort.
<b>Toe-Cap:</b>	Composite
<b>Antiperforation:</b>	Anti perforation textile "0 Perforation"
<b>Insock:</b>	Antistatic with Antibacterial Treatment
<b>Width:</b>	11 Mondopoint
<b>Norm:</b>	EN ISO 20345:2011 CE
<b>Category:</b>	<b>S3</b>
<b>Color:</b>	Black
<b>Sizes:</b>	36-48 (Europe)

Moisture  
Absorbing  
Insoles



IMPACT  
RESISTANT



PENETRATION  
RESISTANT



SLIP  
RESISTANT



OIL  
RESISTANT



ABRASION  
RESISTANT



COMPOSITE TOE CAP



ANTIPERFORATION

#### Category Description

**S3** 200 Joule Toecap Protection. Closed seat region (fully enclosed heel). Antistatic properties. Energy absorption of seat region. Water penetration and water absorption resistance. Plus penetration resistance. Cleated outsole.

Doc. Control:	Rev.:	Date:
	3.2	April 9, 2016

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT FW 9003-3.2

**BORN TOUGH**

A PRODUCT OF





### CAPTAIN - HIGH CUT

Article No.: 73110CV214

Model No.: 8713-4

## CAPTAIN

### TECHNICAL SPECIFICATIONS

Breathable lining with **Antibacterial Treatment** on the insock

Waterproof  
Smooth leather

Polyurethane Double Density Injected – SRC Slipping Resistance, Oil Resistant, Antislip

Strong stitching

 Antiperforation

Polyurethane Double Density Injected – SRC Slipping Resistance Value, Antistatic and Antislip

Shock Absorber

Composite Toe Cap 

Moisture Absorbing Insoles 

**S3**

#### Category Description

**S3** 200 Joule Toecap Protection. Closed seat region (fully enclosed heel). Antistatic properties. Energy absorption of seat region. Water penetration and water absorption resistance. Plus penetration resistance. Cleated outsole.

Doc. Control:	Rev.:	Date:
	3.2	April 9, 2016

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT FW 9003-3.2

**BORN TOUGH**

A PRODUCT OF

  
**PROTECTIVE LINE**