



CAPTAIN - LOW CUT

Article No.: 74110CV215

Model No.: 8712-4

Cavalier™ Captain Safety Footwear is designed to Made from High Quality smooth leather offer optimum comfort during long work hours. Double density PU sole which is anti-slip with deep grroves. Suitable for any nature of harsh working conditions. Low-cut safety shoes provided with breathable inner lining for extra comfort.



COMPOSITION:

- Safety Boots S3, made from selected High Quality Smooth Leather.
- Good Design, lightweight, comfortable, antislip, breathable

FEATURES:

| | |
|------------------|---|
| Upper: | High Quality smooth tanned leather |
| Lining: | Breathable lining |
| Toe-Cap: | Composite |
| Midplate: | Antiperforation textile meeting EN20345 S3 Standards |
| Insock: | Anatomic & Antistatic with Antibacterial Treatment |
| Sole: | Double density PU Sole, antislip with deep grooves |
| Width: | 11 Mondopoint |
| Norm: | EN ISO 20345:2011 CE |
| Category: | S3 |
| Color: | Black |
| Sizes: | 36-48 (Europe) |



IMPACT RESISTANT



PENETRATION RESISTANT



SLIP RESISTANT



OIL RESISTANT



ABRASION RESISTANT



COMPOSITE TOE CAP



ANTIPERFORATION

Category Description

S3 200 Joule Toecap Protection. Closed seat region (fully enclosed heel). Antistatic properties. Energy absorption of seat region. Water penetration and water absorption resistance. Plus penetration resistance. Cleated outsole.

| | | |
|----------------------|--------------|---------------|
| Doc. Control: | Rev.: | Date: |
| | 3.2 | April 9, 2016 |

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT FW 9004-3.2

BORN TOUGH

A PRODUCT OF





CAPTAIN - LOW CUT

Article No.: 74110CV215

Model No.: 8712-4

CAPTAIN

TECHNICAL SPECIFICATIONS

Breathable lining with
Antibacterial Treatment
on the insock

Upper
Waterproof leather


Polyurethane Double
Density Injected – SRC
Slipping Resistance
Value, Oil Resistant

Strongly
double
stitched


Antiperforation
Midplate
EN20345

Shock
Absorber

Polyurethane Double
Density Injected – SRC
Slipping Resistance
Value, Oil Resistant

Composite
Toe-Cap 

Moisture
Absorbing
Insoles



S3

Category Description

S3 200 Joule Toecap Protection. Closed seat region (fully enclosed heel). Antistatic properties. Energy absorption of seat region. Water penetration and water absorption resistance. Plus penetration resistance. Cleated outsole.

| | | |
|---------------|-------|---------------|
| Doc. Control: | Rev.: | Date: |
| | 3.2 | April 9, 2016 |

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT FW 9004-3.2

BORN TOUGH

A PRODUCT OF

