



TRAFFIC CONES

Traffic cones mark Temporary Traffic Control (TTC) Zones, "An area of a highway where road user conditions are changed. It can be use in Work zones, Incident zones, Planned event zones or Special lanes on the roads.



Flow Molded



Injected

SPECIFICATIONS

- Durable and reboundable premium grade PVC constructions
- With or without reflective collars
- Maintenance free
- Pavement gripping bottoms ensure stay in place
- Cones conveniently stack for quick and easy storage and no sticking when removed

Dimensions / Size Chart

Height (Inches)	Base Size L x W (mm)	Flow Molded Nominal Weight (kg)	Injected Molded Nominal Weight (Kg)
12"	210 x 210	0.8 (± .2)	1.2 (± .2)
18"	280 x 280	1 (± .2)	1.5 (± .2)
28"	360 x 360	2 (± .3)	3 (± .3)
36"	360 x 360	4 (± .3)	5 (± .3)

APPLICATIONS

They are often used to create separation or merge lanes during road construction projects or automobile accidents. Also can be use in airports, construction areas and other road works.

Doc. Control:	Rev.: 3.2	Date: April 13, 2016
---------------	-----------	----------------------

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT-FHC-2002 3.2

