

AVES[®]

AV-FS15CL CLEAR FACE SHIELD

Article No.: 3417AV378

The AVES[®] Elvex FS-15CL Clear Molded Hard Coated Lexan Polycarbonate Face Shield with Universal hole pattern! Plus wraparound, splash and impact protection!



TECHNICAL SPECIFICATIONS

Material	: Molded Hard-coated LEXAN PC
Color	: Clear
Thickness	: 0.07 inches
Dimensions	: 8" x 15.5" x .07"
Light Transmission	: VLT = 91% (Clear)
UV protection = 100.0% / 180-380 nm	
IR protection = 8% (Clear)	
Temperature Resistance:	
• Heat distortion temperature, 265 degree F/129°C	
• Brittle temperature, -211 degree F / - 99°C	

Standard: ANSI Z87.1-2010

Note: ANSI standard requires users to wear safety glasses under face shields.

Features:

- Faceshield has a protective hard coating to prevent against scratching.
- Faceshield has Universal Hole Pattern to fit: Headgear and Safety helmet – fits "AV-VB" visor brackets with "AV-SA" slot adaptor for mounting on most slotted helmets.



AV-VB10 Visor Bracket
Article No.: 3481AV392



AV-SA29 Slot Adapters
Article No.: 34182AV394

Application:

- For industrial use to provide 97.5% infra red radiation protection and impact, splash, and 100% UV protection.
- Polycarbonate (PC) material has IR absorbers for use as a weld shade #5 face shield.

Doc. Control:	Rev.:	Date:
	3.2	April 5, 2016

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT EF 2042-3.2

