

**EYE PROTECTION** 





# **AV-SG15 SAFETY EYEWEARS**

Article No.: 6026AV102

AVES® SG15 offers sleek styling, likely to impress today's fashion oriented workers. The close fit and excellent protective features will please employers. AVES® SG15 is one of our most economical glasses should make this one of our most successful styles.

- 100% UV protection
- Universal nose bridge and temple tips
- Complies with ANSI Z87.1-2010 (+) & CE EN-166





AV-SG15C

Clear HC/PC Lens, Black Temples



Grey HC/PC Lens, Black Temples



AV-SG15-I/O

Indoor/Outdoor HC/PC Lens, Black Temples

AV-SG15A

Amber HC/PC Lens, Black Temples

### **STANDARDS**







## **LENS STYLE**

#### **APPLICATION & BENEFIT**



**Clear** - General purpose impact protection for indoor and outdoor use.



**Grey** - General purpose sun lens that reduces sun glare and intense sunlight for outdoor applications.



**Indoor/Outdoor** - Provides 50% glare reduction for workers moving between indoor/outdoor lighting conditions.



**Amber** - Blocks blue light for applications where increased visual contrast is needed. Inspection/ Quality Control, haze and fog.

## **TECHNICAL SPECIFICATION**

Overall Width (hinge-hinge)


Lens thickness : 2.75 mm PD : 68 mm

Lens Base : 10 base curve

Weight : 25 gm
Lens size vertical : 43.137 mm
Lens size diagonal : 67.82 mm
Bridge : 27.5 mm
Temple length (lens-tip) : 121.54mm

Closest point between lens : N/A, Single lens Closest point between temple tips: 65.65 mm

Safety glasses comply with ANSI Z87.1-2010 and most models meet the requirements of CE - EN166. Required test include among others high velocity, high mass impact, lens thickness, lens distortion, and lens light transmission.



This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT EF 2005-3.2





:132.15 mm