




### AV-226B FFP2 MASK

Article No.: 27106AV190

**AVES® AV-226B FFP2 NR D filtering facepieces provides effective respiratory protection in industrial environments where workers will be exposed to non-volatile solid and/or liquid particles (dusts, mists, fumes).**



#### DESCRIPTION

- Cup shape.
- Headband made by two elastic straps.
- Adjustable nose-clip between the filter material layers and soft inner lining on nose, to ensure a good face seal over a range of face sizes.
- Carbon layer allows to keep disagreeable smell of organic and inorganic gas and vapours present in low concentration
- Exhalation valve, with a low breathing resistance, which drops heat and humidity inside the respirator, makes breathing easier and makes the respirator suitable for hot humid work place.
- NR marking to specify that the facepieces is a single use item and it is Not Reusable for more than one work shift.
- D marking to specify that the facepieces meets the clogging resistance requirements and then it offers an high level of filtering efficiency also in very dusty environments.
- CE approved to new EN 149:2001+A1:2009 standard.

#### MATERIAL

The following materials are used in the production of **AVES AV-226B** filtering facepieces:

- Filter: filtering material in layers, non irritating, polypropylene non-woven fabric
- Nose clip: reinforced plastic material
- Face seal: foam rubber
- Straps: Thermoplastic elastomer
- Staples: Steel
- No-odour filter : active charcoal
- Valve/Valve diaphragm: polypropylene /para rubber
- Weight: 19 g

EN 149:2001+A1 tests		FFP2 NR D Requirements	AV-226B FFP2 NR D
Total filtering efficiency (%)		> 92	96
Breathing resistance (mbar)	inhal. 30 l/min	< 0,7	0,4
	inhal. 95 l/min	< 2,4	1,5
	exhal. 160 l/min	< 3,0	1,7
	after clogging inhal. 95 l/min	< 5,0	4,0
Filter material efficiency (DOP) (%)	after 3 min	> 94	96
	after 63 min (long exposure)	> 94	95
	after clogging	> 94	96

#### LEVEL OF PROTECTION

**AVES AV-226B FFP2 NR D** filtering facepieces is suitable for protection against non-volatile solid and/or liquid particles up to 10\* times the Threshold Limit Value (TLV-TWA).

\*= APF, Assigned Protection Factor (in accordance to EN 529 :2005 standard – value for Italy).

It can be used to keep unpleasant odours of gases & organic vapours in concentrations below the TLV level

#### STANDARDS

**AVES AV-226B FFP2 NR D** filtering facepieces meets the requirements of the European Directive 89/686/EEC (PPE) and is thus CE marked, as a PPE of III category, according to EN149:2001+A1:2009 standard. CE Certification (Art.10) and control (Art.11.B) have been issued by Italcert S.r.l. (Notified body n°0426). AVES certified his own Quality Management System according to ISO 9001:2008 regulation

Doc. Control:	Rev.:	Date:
	3.2	April 6, 2016

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT RP 4023-3.2





### AV-226B FFP2 MASK

Article No.: 27106AV190

#### TECHNICAL DETAILS



In order to reduce the chance of product contamination (required by various industries among which the pharmaceutical and the food industries), the internal noseclip is set between two layers of fabric to reduce as much as possible the aluminum parts of the PPE.



The greater amount of fabric, emphasized by the folds on the surfaces of the filtering facepiece, and the high concavity of the mask increase the PPE duration.



The shell filtering facepieces offer a greater user comfort and avoid the feeling of oppression of the PPE thanks to the substantive distance between the inner surface of the filtering facepiece and the user's mouth.

Filtering facepieces passed Dolomite dust clogging test. Lower breathing resistance, higher duration.

Active charcoal layer: protection against gas contaminants in low concentration.

#### CLEANING

AVES AV-226B FFP2 NR D filtering facepieces is NR marked, i.e. it can not be used for more than one shift; so throw it away at the end of each shift and do not clean.

#### STORAGE AND TRANSPORTATION

AVES AV-226B FFP2 NR D particle filtering facepieces has a shelf life of 5 years. End of shelf life (expiry date) is marked on the product packaging.

Product should be stored in clean, dry conditions within the temperature range: +5°C to +40°C with a maximum relative humidity of 60%.

When storing or transporting this product, use original packaging provided

#### CERTIFICATION TEST

- Efficiency of filter material
- Total filtering efficiency
- Breathing resistance
- Clogging
- Flammability

#### WARNINGS

1. The operator must be trained to the proper use of the filtering facepieces, before use it.
2. This product does not protect the operator against gases and vapours. For gas and vapours protection are necessary the gas respirators.
3. Not to be used in atmospheres containing less than 17% oxygen.
4. Do not use when the concentration of the contaminants is immediately dangerous for life or health.
5. Do not use in explosive atmosphere and to escape.
6. Leave the workplace immediately:
  - if breathing becomes difficult;
  - if dizziness or other distress occur.
7. Do not alter or modify the product in any way.
8. Discard and replace the mask if it becomes damaged, if breathing becomes difficult and in any case after 8 hours work if the facepieces is NR type (max 8 hours).
9. Operator must be clean shaven as facial hair will affect the efficiency of the product.
10. Store the filtering facepieces in a dry and clean room at a temperature within +5 °C and + 40 °C and relative humidity <60%. If stored correctly and in the original packaging the product has a shelf life of 10 years and 5 years for models with carbon layer.
11. Cleaning: the filtering facepieces designed as R D, are reusable for more than one work shift, so they must be cleaned before to store them in a dry and clean place. For cleaning, use a wet wipes, of the type usually commercialized (with ingredients as Aqua, Propylene Glycol, Capric Glycerides, Parfum), to delicately clean the inner gasket.

Doc. Control:	Rev.:	Date:
	3.2	April 6, 2016

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT RP 4023-3.2

