

INHERENTLY HEAT & FLAME RETARDANT

PERSONAL PROTECTIVE EQUIPMENT



FR LADIES HEADSCARF Article No.: 1656FT80

Armor[®] inherently flame-retardant and Flash high temperature resistant garments do not support cumbustion in the air, melt or drip due to their molecular structure and its flame retardant characteristics cannot be washed away. Our range is designed to cater for working conditions around the world as garments are offered in various designs and options.

Flame resistant clothing made with **Flash Armor**[®] provides valuable peace-of-mind, which enables those who wear it to focus on the job at-hand & perform to their fullest potential.



A breathable workwear with properties of inherent heat & flame retardant. This garment is a preferred choice of people working from the oil & gas, petrochemical, refinery industries, as well as an excellent choice for electric and power generation industries.

Inherently flame resistant – FR properties are built in and won't wash or wear out. Comfortable to wear - Soft & breathable. Roomy sizing patterns allow for a great fit. Exceptional durability – Outstanding laundered appearance - Fabric retains its like new look and maintains permanent pressed appearance. Excellent Value - Long life cycle & great durability.

COMPOSITION

Fabric Grade: DuPont[™] Nomex[®] IIIA 93% Nomex[®], 5% Kevlar[®], 2% P140 (Antistatic) Fabric Weight: 200 gsm / 6.0 Oz

STYLE & DESIGN

Rectangular shape

COLORS

• Dimension: 60cm (L) x 180cm (H)

PPE CUSTOMIZATION PROGRAM



Corporate Logo / URSP Name Placement

INTERNATIONAL STANDARDS

A1 - Limited Flame Spread **B1** - Convective Heat C1 - Radiant Heat

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) Date: Rev.: March 26, 2016

60 cm

omex

covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval. FT FR 6143-3.2

180 cm

FLOWTRONIX (FT)

3.2

Doc. Control:

WWW.FLOWTRONIX.COM

11612 EN ISO A1, B1, C1

WE ARE TRUSTED TO DELIVER QUALITY

A PRODUCT OF